Technical Memorandum BCWA



| Date: | March 3, 2020 |
|-------|--|
| To: | Bear Creek Watershed Association |
| From: | Russell N. Clayshulte, Manager |
| Re: | BCWA TM 2019.07 Barr Milton TMDL Summary |

Contents

| Purpose of | f Site 45 Monitoring | 2 |
|-------------|--|---|
| Phosphoru | s Compliance with BMW TMDL | 2 |
| 2019 Flow | Estimate | 2 |
| 2019 Nutri | ients | 3 |
| E. coli Tre | nd BCWA Site 45 | 5 |
| Table 1 | Model Dradiation Compared with DCWA Data | 2 |
| Table 7 | Phosphorus and Nitrogen Load Estimates Per Vear | |
| Table 3 | Summary Data 2010-2019 | |
| Table 4 | E. coli Geometric Mean Summary | 5 |
| Figure 1 | BCWA Site 45 is located below the Weir in the Outfall Trace | 1 |
| Figure 2 | BCWA Site 45 Sampling Location below Weir. | 2 |
| Figure 3 | Sediment and Nutrient Load Typically Associated with Spring Flows | 2 |
| Figure 4 | Flow Trend at BCWA Site 45 | 3 |
| Figure 5 | Total Phosphorus Trend | 3 |
| Figure 6 | Total Nitrogen Trend | 4 |
| Figure 7 | E.coli at Site 45 vs. Site 90 at Wadsworth (Site 45 number very low) | 5 |



Figure 1 BCWA Site 45 is located below the Weir in the Outfall Trace



Figure 2

BCWA Site 45 Sampling Location below Weir.

Purpose of Site 45 Monitoring

The Bear Creek Watershed is in the defined "data" shed for the BMW pH/DO TMDL. The Bear Creek Watershed boundary is defined in *BCWA Policy 13 Watershed Boundary*. Discharge from Bear Creek Reservoir is identified as a "point" source and input to the BMW pH/DO TMDL and model. As such, the BCWA site 45 is identified as a source that contributes about 1.8 % of the external load of Total Phosphorus (See Table 1). The BMW pH/DO TMDL defines the contribution of Total Phosphorus from Bear Creek for both Barr Lake and Milton Reservoir at 1,167 kg/year or 2,672.7 pounds/year. The Association uses site 45 data to estimate Bear Creek Reservoir mass-balance loading and discharge.

Phosphorus Compliance with BMW TMDL

In the period from 2000 through 2019, the average Total Phosphorus at BCWA site 45 was 2,604 pounds/year (Table 2). Problematic years are 2007, 2013, 2015 and 2016. In 2007, the flow predictions were used for the downstream Sheridan gage (Table 2 and Figure 3). Although the Association believes the actual flow at site 45 was less than measured at Sheridan, the total load would still exceed the target of 2,672.7 pound/year.

The Total Phosphorus load target at BCWA site 45 was met in 12 out of 19 years of reviewed data. The target Total Phosphorus listed in the BMW pH/DO TMDL can be met under most hydrologic conditions and within the expectations of the BCWA management program. The BMW pH/DO TMDL expects any reduction in this target Total Phosphorus load will occur by in-canal treatment in the Barr-Milton Watershed prior to discharge into those waterbodies.

2019 Flow Estimate

The average inflow into Bear Creek Reservoir from both Turkey Creek & Bear Creek (1987-2019) was 29,7693 acre-feet per year. The highest flow was in 2015 with 118,925 acre-feet flowed through the reservoir. In 2019, 15,3580 acre-feet flowed from the reservoir. There is a state DNR staff gage above the weir at site 45, which allows the Association to monitor flow at the monitoring station.





Bear Creek Watershed Association Page | 3



Figure 4 Flow Trend at BCWA Site 45

2019 Nutrients

The Association collects Total Nitrogen/ Total Phosphorus pairs for 12 months/year (unless no flow or completely frozen) at BCWA site 45. The Association maintains a spreadsheet (*BCWA MSD06 Site 45 Data Summary*) for BCWA site 45 that contains water quality data and nutrient loading estimates (Summary data is shown in Table 3, spreadsheet available upon request).

In 2019 the average Total Phosphorus discharged from the reservoir as measured at BCWA site 45 was 36.4 ug/l. this equates to about 687 pounds/year. Figure 5 and table 2 shows the Total Phosphorus loading at BCWA site 45. Figure 5 also shows the compliance record for Total Phosphorus.

Since nitrogen is an issue, the Association estimated the nitrate loading at BCWA site 45 from 2000-2016 and Total Nitrogen from (2011-2019). In 2019 the average Total Nitrogen concentration discharged from the reservoir as measured at BCWA site 45 was 656 ug/l. This equates to about 26,728 pounds/year. Figure 6 and Table 2 shows the Total Nitrogen loading at BCWA site 45.

Table 1Model Prediction Compared with BCWA Data

| | Average | Total T | P TMAL Load | Barr Load | | % of | Milton | | % of |
|---------------|---------|---------|-------------|-----------|-------------|--------|--------|-------------|--------|
| Source | Conc. | Kg/yr | | | | Total | Kg/yr | | Total |
| | (ug/l) | | Pounds/Year | Kg/yr. | Pounds/Year | Load | | Pounds/Year | Load |
| Model Bear | 32.80 | 1 167 | 2 673 | 1.001 | 2 505 | 1 60% | 76 | 167.5 | 0.20% |
| Creek Site 45 | 32-80 | 1,107 | 2,075 | 1,091 | 2,303 | 1.0070 | 70 | 107.5 | 0.2070 |
| BCWA Bear | 29.1 | 1271 | 2 801 | | | | | | |
| Creek Site 45 | 30.1 | 12/1 | 2,001 | | | | | | |





| | Total Phosphorus | Nitrate | Total Nitrogen |
|---------|------------------|-------------|----------------|
| | Pounds/Year | Pounds/Year | Pounds/year |
| 2000 | 1,243 | 23,146 | |
| 2001 | 1,847 | 17,736 | |
| 2002 | 187 | 3,182 | |
| 2003 | 2,856 | 2,856 | |
| 2004 | 2,667 | 3,569 | |
| 2005 | 2,094 | 22,936 | |
| 2006 | 776 | 6,837 | |
| 2007 | 6,047 | 57,496 | |
| 2008 | 991 | 16,470 | |
| 2009 | 1,361 | 18,576 | |
| 2010 | 2,259 | 32,148 | |
| 2011 | 624 | 3,467 | 10,632 |
| 2012 | 260 | 4,315 | 7,897 |
| 2013 | 7,627 | 22,576 | 80,028 |
| 2014 | 1,841 | 27,821 | 63,229 |
| 2015 | 10,320 | 84,081 | 172,116 |
| 2016 | 4,369 | | 84,580 |
| 2017 | 3,051 | | 36,460 |
| 2018 | 409 | | 15,538 |
| 2019 | 1,262 | | 26,728 |
| Average | 2,604 | 21,701 | 66,780 |

Table 2Phosphorus and Nitrogen Load Estimates Per Year



Figure 6

Total Nitrogen Trend

Table 3Summary Data 2010-2019

| | Avg | Median | Max | SD | Min |
|---|-------|--------|--------|-------|-------|
| Temperature, °C | 13.8 | 14.7 | 24.1 | 6.9 | 1.3 |
| Total Suspended Solids, mg/L | 8.5 | 6.6 | 94.7 | 8.9 | 0.0 |
| Specific Conductance us/cm | 407.2 | 386.0 | 893.0 | 152.2 | 147.0 |
| Fecal Coliforms, colonies per 100 ml (Geo Mean) | 7 | | | | |
| E. coli cts/100 ml (Geo Mean) | 2 | | | | |
| Dissolved Oxygen, mg/L | 9.1 | 9.0 | 15.5 | 2.0 | 3.3 |
| pH | 8.3 | 8.3 | 9.4 | 0.4 | 7.0 |
| Total ammonia-nitrogen, ug/L | 55.2 | 39.9 | 403.0 | 55.7 | 3.0 |
| Nitrate-nitrogen, ug/L | 268.9 | 187.9 | 1700.2 | 254.1 | 0.0 |
| Soluble Reactive Phosphorus (SRP), ug/l | 12.5 | 6.6 | 76.4 | 14.0 | 0.1 |
| Total Dissolved Phosphorus (TDP), ug/l | 19.0 | 13.6 | 96.0 | 16.5 | 2.0 |
| Total Particulate Phosphorus (TPP), ug/l | 17.3 | 12.4 | 136.8 | 19.2 | 2.6 |
| Total Phosphorus (Total P), ug/l | 38.2 | 30.0 | 259.0 | 30.8 | 2.0 |
| Total Nitrogen, ug/l | 712.1 | 650.0 | 2241.0 | 270.1 | 342.0 |

E. coli Trend BCWA Site 45

Table 4 shows the E. coli geometric mean data at BCWA site 45 from 2004-2019. Figure 7 compares E. coli data at BCWA site 45 with the downstream Wadsworth BCWA site 90. There is no E. coli problem associated with discharge from Bear Creek Reservoir.

Table 4E. coli Geometric Mean Summary

BCWA Site 45 E. Coli Geometric mean cts/100ml

| | J-F | M-A | M-J | J-A | S-O | N-D | Annual | | |
|---|-----|-----|-----|-----|-----|-----|--------|--|--|
| 2004-2014 | | | | | | | 3 | | |
| 2012 | | | | | | 1 | | | |
| 2013 | 0 | 6 | 2 | 9 | 2 | 1 | 2 | | |
| 2014 | 2 | 2 | 5 | 2 | 1 | 14 | 3 | | |
| 2015 | 3 | 3 | 8 | 2 | 1 | 6 | 3 | | |
| 2016 | 1 | 2 | 2 | 9 | 6 | 7 | 3 | | |
| 2017 | 1 | 1 | 5 | 11 | 1 | 1 | 2 | | |
| 2018 | 2 | 1 | 1 | 3 | 3 | 3 | 2 | | |
| 2019 | 6 | 2 | 3 | 3 | 2 | 2 | 3 | | |
| I D C W C' + D C I S E = 1' (M D V / 100 1) | | | | | | | | | |

LBCW Site BCL5 E. coli (MPN/100ml)

| | J-F | M-A | M-J | J-A | S-O | N-D | Annual |
|------|-----|-----|-----|-----|-----|-----|--------|
| 2013 | | | 62 | 36 | 54 | | 46 |



